

Technical data: UX Super trailed sprayers

Model	UX 4201 Super	UX 5201 Super	UX 6201 Super	UX 11201 Super
Nominal volume (l)	4,200	5,200	6,200	11,200
Tank capacity (l)	4,600	5,600	6,560	12,000
Fresh water tank (l)	580			900
Working width (m)	21 – 40			24 – 40
Transport height (m)	3.52 – 3.79		3.75 – 3.90	3.90
Transport length (m) with Super-L2 boom	6.85 – 7.50			9.70
Transport width (m) Super-L2 boom:	3-section: 2,40 4-section: 2.65		3-section: 2,60 4-section: 2.80	2.85
Transport width (m) Super-L3 boom:	2.55		2.75	
Empty weight (kg)	3,500 – 4,998	3,707 – 5,042	3,959 – 5,221	7,870 – 8,284
Pump capacity (l/min)	520			700
Max. suction capacity (l/min)	700			900
Ground clearance	up to 0.82 m			
Spraying height	0.5 – 2.5 m			
Operating pressure, max. (bar)	10			

Illustrations, content and technical data are not binding! Deviations of technical data are possible depending on the equipment. The illustrations may deviate from the requirements for local road traffic regulations.



The smaller alternatives – The UX Special and UG trailed sprayer

For smaller farms, AMAZONE offers the UX Special and UG trailed sprayers with tank capacities from 2,200 to 5,200 litres. Further information can be found in the machine specific brochures.